



Articulaciones de horquilla DIN 71 751

Con perno de chaveteado, galvanizado

a (mm)	b x c (mm)	d (mm)	e (mm)	f (mm)	Art. N°	U/E
10	M 5 x 20	30	M 5	5	268 005 20	10
12	M 6 x 12	24	M 6	6	268 006 12	
12	M 6 x 24	36	M 6	6	268 006 24	
16	M 8 x 16	32	M 8	8	268 008 16	
16	M 8 x 32	48	M 8	8	268 008 32	
20	M 10 x 20	40	M 10	10	268 010 20	5
20	M 10 x 40	60	M 10	10	268 010 40	
24	M 12 x 24	48	M 12	12	268 012 24	
24	M 12 x 48	72	M 12	12	268 012 48	
27	M 14 x 28	56	M 14	14	268 014 28	
27	M 14 x 56	86	M 14	14	268 014 56	

Con perno de chaveteado, rosca a la izquierda, galv.

a (mm)	b x c (mm)	d (mm)	e (mm)	f (mm)	Art. N°	U/E
10	M 5 x 20	30	M 5	5	268 105 20	5
12	M 6 x 12	24	M 6	6	268 106 12	
16	M 8 x 16	32	M 8	8	268 108 16	
20	M 10 x 20	40	M 10	10	268 110 20	
24	M 12 x 24	48	M 12	12	268 112 48	
27	M 14 x 28	56	M 14	14	268 114 28	

Articulaciones acodadas DIN 71 802

Con resorte fiador, forma A, rosca derecha, galv.

a (mm)	b x c (mm)	d (mm)	g (mm)	h (mm)	Art. N°	U/E
8	M 5 x 10	9	8	22	268 205 20	10
10	M 6 x 12	11	10	25	268 206 12	
13	M 8 x 16	13	13	30	268 208 16	
16	M 10 x 19	16	16	35	268 210 19	5
16	M 12 x 19	16	16	35	268 212 19	

Con resorte fiador y asa de fijación, versión larga, galv.

a (mm)	b x c (mm)	d (mm)	g (mm)	h (mm)	Art. N°	U/E
10	M 6 x 12	9	10	38	268 306 12	10
13	M 8 x 16	11	13	46	268 308 16	
16	M 10 x 19	13	16	52	268 310 19	5

Con resorte fiador y asa de fijación, forma AS, galv.

a (mm)	b x c (mm)	d (mm)	g (mm)	h (mm)	Art. N°	U/E
8	M 5 x 10	9	8	22	268 505 10	10
10	M 6 x 12	11	10	25	268 506 12	
13	M 8 x 16	13	13	30	268 508 16	
16	M 10 x 19	16	16	35	268 510 19	5

Con resorte fiador y asa de fijación, forma AS, rosca izquierda, galvanizado.

a (mm)	b x c (mm)	d (mm)	g (mm)	h (mm)	Art. N°	U/E
8	M 5 x 10	9	8	22	268 605 10	5
10	M 6 x 12	11	10	25	268 606 12	
13	M 8 x 16	13	13	30	268 608 16	
16	M 10 x 19	16	16	35	268 610 19	