

## PASADOR ACERO ELÁSTICO

Nominal dia. d in mm	l in mm	s in mm	a in mm	d <sub>1</sub> in mm	Bare steel Art. No.	P. Qty.
4.5	30	1	1	2.9	<b>0475 45 30</b>	100
4.5	40	1	1	2.9	<b>0475 45 40</b>	100
4.5	50	1	1	2.9	<b>0475 45 50</b>	100
5	5	1	1.1	3.4	<b>0475 5 5</b>	500
5	6	1	1.1	3.4	<b>0475 5 6</b>	200
5	8	1	1.1	3.4	<b>0475 5 8</b>	500
5	10	1	1.1	3.4	<b>0475 5 10</b>	500
5	12	1	1.1	3.4	<b>0475 5 12</b>	200
5	14	1	1.1	3.4	<b>0475 5 14</b>	100
5	16	1	1.1	3.4	<b>0475 5 16</b>	100
5	18	1	1.1	3.4	<b>0475 5 18</b>	100
5	20	1	1.1	3.4	<b>0475 5 20</b>	100
5	22	1	1.1	3.4	<b>0475 5 22</b>	100
5	24	1	1.1	3.4	<b>0475 5 24</b>	100
5	25	1	1.1	3.4	<b>0475 5 25</b>	100
5	26	1	1.1	3.4	<b>0475 5 26</b>	100
5	28	1	1.1	3.4	<b>0475 5 28</b>	100
5	30	1	1.1	3.4	<b>0475 5 30</b>	100
5	32	1	1.1	3.4	<b>0475 5 32</b>	100
5	36	1	1.1	3.4	<b>0475 5 36</b>	100
5	40	1	1.1	3.4	<b>0475 5 40</b>	100
5	45	1	1.1	3.4	<b>0475 5 45</b>	100
5	50	1	1.1	3.4	<b>0475 5 50</b>	100
5	55	1	1.1	3.4	<b>0475 5 55</b>	100
5	60	1	1.1	3.4	<b>0475 5 60</b>	100
5	70	1	1.1	3.4	<b>0475 5 70</b>	100
5	80	1	1.1	3.4	<b>0475 5 80</b>	100
6	8	1.2	1.4	4.0	<b>0475 6 8</b>	200
6	10	1.2	1.4	4.0	<b>0475 6 10</b>	100
6	12	1.2	1.4	4.0	<b>0475 6 12</b>	100
6	14	1.2	1.4	4.0	<b>0475 6 14</b>	500
6	16	1.2	1.4	4.0	<b>0475 6 16</b>	100
6	18	1.2	1.4	4.0	<b>0475 6 18</b>	100
6	20	1.2	1.4	4.0	<b>0475 6 20</b>	100
6	22	1.2	1.4	4.0	<b>0475 6 22</b>	100
6	24	1.2	1.4	4.0	<b>0475 6 24</b>	100
6	25	1.2	1.4	4.0	<b>0475 6 25</b>	100
6	26	1.2	1.4	4.0	<b>0475 6 26</b>	100
6	28	1.2	1.4	4.0	<b>0475 6 28</b>	100
6	30	1.2	1.4	4.0	<b>0475 6 30</b>	100
6	32	1.2	1.4	4.0	<b>0475 6 32</b>	100
6	36	1.2	1.4	4.0	<b>0475 6 36</b>	100
6	40	1.2	1.4	4.0	<b>0475 6 40</b>	100
6	45	1.2	1.4	4.0	<b>0475 6 45</b>	100
6	50	1.2	1.4	4.0	<b>0475 6 50</b>	100
6	55	1.2	1.4	4.0	<b>0475 6 55</b>	250
6	60	1.2	1.4	4.0	<b>0475 6 60</b>	100
6	65	1.2	1.4	4.0	<b>0475 6 65</b>	250
6	70	1.2	1.4	4.0	<b>0475 6 70</b>	100
6	75	1.2	1.4	4.0	<b>0475 6 75</b>	250
6	80	1.2	1.4	4.0	<b>0475 6 80</b>	100

## ISO 8752

Nominal dia. d in mm	l in mm	s in mm	a in mm	d <sub>1</sub> in mm	Bare steel Art. No.	P. Qty.
6	85	1.2	1.4	4.0	<b>0475 6 85</b>	250
6	90	1.2	1.4	4.0	<b>0475 6 90</b>	50
6	95	1.2	1.4	4.0	<b>0475 6 95</b>	250
7	30	1.5	1.8	4.5	<b>0475 7 30</b>	250
7	40	1.5	1.8	4.5	<b>0475 7 40</b>	50
7	45	1.5	1.8	4.5	<b>0475 7 45</b>	500
7	50	1.5	1.8	4.5	<b>0475 7 50</b>	50
7	60	1.5	1.8	4.5	<b>0475 7 60</b>	50
7	70	1.5	1.8	4.5	<b>0475 7 70</b>	50
7	80	1.5	1.8	4.5	<b>0475 7 80</b>	50
8	10	1.5	2.4	5.5	<b>0475 8 10</b>	500
8	12	1.5	2.4	5.5	<b>0475 8 12</b>	500
8	14	1.5	2.4	5.5	<b>0475 8 14</b>	500
8	16	1.5	2.4	5.5	<b>0475 8 16</b>	100
8	18	1.5	2.4	5.5	<b>0475 8 18</b>	500
8	20	1.5	2.4	5.5	<b>0475 8 20</b>	100
8	22	1.5	2.4	5.5	<b>0475 8 22</b>	500
8	24	1.5	2.4	5.5	<b>0475 8 24</b>	100
8	25	1.5	2.4	5.5	<b>0475 8 25</b>	250
8	26	1.5	2.4	5.5	<b>0475 8 26</b>	100
8	28	1.5	2.4	5.5	<b>0475 8 28</b>	250
8	30	1.5	2.4	5.5	<b>0475 8 30</b>	100
8	32	1.5	2.4	5.5	<b>0475 8 32</b>	100
8	36	1.5	2.4	5.5	<b>0475 8 36</b>	100
8	40	1.5	2.4	5.5	<b>0475 8 40</b>	50
8	45	1.5	2.4	5.5	<b>0475 8 45</b>	50
8	48	1.5	2.4	5.5	<b>0475 8 48</b>	100
8	50	1.5	2.4	5.5	<b>0475 8 50</b>	50
8	55	1.5	2.4	5.5	<b>0475 8 55</b>	50
8	60	1.5	2.4	5.5	<b>0475 8 60</b>	50
8	65	1.5	2.4	5.5	<b>0475 8 65</b>	250
8	70	1.5	2.4	5.5	<b>0475 8 70</b>	50
8	75	1.5	2.4	5.5	<b>0475 8 75</b>	250
8	80	1.5	2.4	5.5	<b>0475 8 80</b>	50
8	85	1.5	2.4	5.5	<b>0475 8 85</b>	200
8	90	1.5	2.4	5.5	<b>0475 8 90</b>	50
8	95	1.5	2.4	5.5	<b>0475 8 95</b>	100
10	10	2	2.4	6.5	<b>0475 10 10</b>	500
10	12	2	2.4	6.5	<b>0475 10 12</b>	500
10	14	2	2.4	6.5	<b>0475 10 14</b>	500
10	16	2	2.4	6.5	<b>0475 10 16</b>	500
10	18	2	2.4	6.5	<b>0475 10 18</b>	500
10	20	2	2.4	6.5	<b>0475 10 20</b>	100
10	22	2	2.4	6.5	<b>0475 10 22</b>	500
10	24	2	2.4	6.5	<b>0475 10 24</b>	500
10	26	2	2.4	6.5	<b>0475 10 26</b>	500
10	28	2	2.4	6.5	<b>0475 10 28</b>	100
10	30	2	2.4	6.5	<b>0475 10 30</b>	50/100
10	32	2	2.4	6.5	<b>0475 10 32</b>	100
10	36	2	2.4	6.5	<b>0475 10 36</b>	50
10	40	2	2.4	6.5	<b>0475 10 40</b>	50