



Swivel Bolt Clamp

for hoses with a high level of hardness or inserts made of metal or plastic



Application

- Lines carrying air
- Exhaust gas system
- Retainer/Fastener

Advantages

Extremely high tightening force

Secure connection of hard hoses as well

Rounded edges/hose bridge

Prevents injury and hose damage

Technical Data

Design	W1	W5
Material of strap	1.0934 alu./zinc	1.4751 stainless-steel A5
Material of screw	steel, galvanized	1.4751 stainless-steel A5
Screw type	external hex.	Allen head
Size	strap width 18 mm = 8 mm	
	strap width 20 mm = 10 mm	
	strap width 25 mm = 13 mm	

Delivery Overview W1

Clamping range in mm	Strap width in mm	Art. No.	P. Qty.
19 - 21	18	0537 118 020	20
23 - 25		0537 118 024	
25 - 27		0537 118 026	
29 - 31		0537 118 030	
31 - 34		0537 118 033	
34 - 37		0537 118 036	
40 - 43		0537 118 042	
43 - 47	20	0537 120 045	15
47 - 51		0537 120 049	
51 - 55		0537 120 053	
55 - 59		0537 120 057	

Clamping range in mm	Strap width in mm	Art. No.	P. Qty.
59 - 63	20	0537 120 061	15
63 - 68		0537 120 066	
68 - 73		0537 125 071	
73 - 79		0537 125 076	
79 - 85	25	0537 125 082	10
85 - 91		0537 125 088	
91 - 97		0537 125 094	
97 - 104		0537 125 101	6
104 - 112		0537 125 108	
112 - 121		0537 125 117	
121 - 130		0537 125 126	

Delivery Overview W5

Clamping range in mm	Strap width in mm	Art. No.	P. Qty.
68 - 73	25	0537 325 071	6

- Specially designed for the suction hoses of food transporters