









CABLE CONNECTORS, NON-INSULATED

Flat plug lug						
Appearance	Connection in mm	Hole dia. in mm	Material	Surface	Art. No.	P. Qty.
	1 x 6.3 x 0.8	5.2	Flat plug: CuZn	Flat plug: bare	0558 504 9	50
		4.2	CuZn	Bare	0558 160 60	100
		5.2			0558 160 61	
		wrench size 6			0558 173 0	
	2 x 6.3 x 0.8	8.4	CuZn	Sn (tinned)	0558 177 4	100
	2 x 6.3 x 0.8	5.2		Sn (tinned)	0558 193 5	




Storable in ORSY®

Ring lug						
Appearance	in mm ²	Flange hole	Material	Surface	Art. No.	P. Qty.
	1.5 - 2.5	M 4	CuZn	Bare	0558 521 5	100
		M 5			0558 521 7	
		M 6			0558 521 9	
		M 8			0558 522 1	


Storable in ORSY®

Butt connector with crimp connection						
Appearance	in mm ²	Length in mm	Material	Surface	Art. No.	P. Qty.
	0.2 - 0.35	Approx. 18	CuSn	Sn (tinned)	0558 516 0	100
	0.5 - 1.0				0558 516 1	
	1.5 - 2.5				0558 516 2	

Storable in ORSY®

Connection accessories for ignition cable, 7 mm dia.						
Appearance	Version	Material	Surface	Art. No.	P. Qty.	
	Ignition cable contact, 3.9 mm dia.	CuSn	Bare	0558 535 1	100	
	SAE spark plug connector	C55/St 3 LG BK	Sn (tinned)	0558 569 5	50	
	Spark plug distributor connector with snap connection	CuZn	Ni (nickel-plated)	0558 501 3	100	

Storable in ORSY®

LEAR GSK							
Plug connector system for contacting flat plug-in fuse inserts as per DIN 72581							
Appearance	in mm ²	Current capacity	No. of poles	Material	Spring material	Art. No.	P. Qty.
	1.5 - 2.5	Max. 40 A	1	CuCrSiTi	FeCrNi	0558 719 102	25
	2.5 - 4.0					0558 719 103	

Storable in ORSY®

Note:

AMP, AMP MCP, AMPMODU are trademarks.