

AMP Junior Power Timer Contact/Flat Plug 2.8

Plug-in connector systems, 2.8 mm, with symmetrical locking lugs, * for single-wire seals

ORSY	in mm ²	Insul. dia. in mm	Seal dia. in mm	Plug in mm	Material	Surface	Art. No.	P. Qty
	0.5 - 1.0	1.4 - 2.3	_	-	CuSn/CrNi	Sn (tin-plated)	0558 991 15	100
		1.4 - 2.7	3.40				0558 190 15*	
		1.4 - 2.1	_		CuSn	Sn (tin-plated) gold-plated	0558 190 2	
			3.40				0558 190 1*	
			_			Sn (tin-plated) silver-plated	0558 190 151	
	1.5 - 2.5	2.1 - 3.1		2.8 × 0.8	CuSn/CrNi	Sn (tin-plated)	0558 991 16	
		2.0 - 3.0	3.40		CuSn		0558 190 85*	
	0.5 - 1.0	1.4 - 2.1	_		CuFe		0558 190 81	
		1.4 - 2.7	3.40				0558 190 16*	
		1.4 - 2.1	_		CuSn	Sn (tin-plated) gold-plated	0558 190 8	
		1.4 - 2.7	3.40				0558 190 83*	
		1.4 - 2.1	_			Sn (tin-plated) silver-plated	0558 190 82	
	1.5 - 2.5	2.2 - 3.0			CuFe	Sn (tin-plated)	0558 190 84	
			3.40				0558 190 86*	

Additional recommended products:

Releasing Tool Single-Wire Seals Art. No. 0713 558 312 Art. No. 0558 991 4..

Flat Plug 2.8

Plug-in connector systems, 2.8 mm, with asymmetrical locking lugs, * for single-wire seals

CRESY	in mm ²	Insul. dia. in mm	Seal dia. in mm	Plug in mm	Material	Surface	Art. No.	P. Qty
	0.5 - 1.0	1.4 - 2.0	_	2.8 x 0.8	CuFe	Sn (tin-plated)	0558 192 102	100
	1.5 - 2.5	2.1 - 2.9					0558 192 103	
	0.5 - 1.0	1.4 - 2.0	3.40				0558 192 105*	100
	1.5 - 2.5	2.1 - 2.9					0558 192 106*	

Additional recommended products:

Releasing Tool Single-Wire Seals

Art. No. 0713 558 412 Art. No. 0558 991 4..

AMP Junior Timer Contact 2.8

Plug-in connector systems, 2.8 mm, with one locking lug

ORSY	in mm ²	Insul. dia. in mm	Plug in mm	Material	Surface	Art. No.	P. Qty.
	0.5 - 1.5	2.0 - 3.0	2.8 × 0.8	CuSn	Sn (tin-plated)	0558 990 9	- 100
	0.5 - 1.0	1.5 - 2.1				0558 996 7	
	1.5 - 2.5	3.0 - 4.3				0558 996 9	

Additional recommended products:

Releasing Tool

Art. No. 0713 558 212