

## Brocas Helicoidales en Pulgadas



HSS DIN 338

Tipo N

$R \leq 800 \text{ N/mm}^2$

Acero: HSS fresado y rectificado

Dureza: 64-65 HRC

Acabado: Brillante.

Ángulo: 135°

Para taladrar aceros de construcción, de fácil mecanización, fundición maleable

Ø (inch)	Ø (mm)	L1 (inch)	L2 (inch)	Art. N°	U/E
1/16	1,59	1"-7/8	7/8	00625 00 116	1
5/64	1,98	2"	1"	00625 00 564	
3/32	2,38	2"-1/4	1"-1/4	00625 00 332	
7/64	2,78	2"-5/8	1"-1/2	00625 00 764	
1/8	3,17	2"-3/4	1"-5/8	00625 00 18	
9/64	3,57	2"-7/8	1"-3/4	00625 00 964	
5/32	3,97	3"-1/8	2"	00625 00 532	
3/16	4,76	3"-1/2	2"-5/16	00625 00 316	
7/32	5,56	3"-3/4	2"-1/2	00625 00 732	
1/4	6,35	4"	2"-3/4	00625 00 14	
5/16	7,94	4"-1/2	3"-3/16	00625 00 516	
11/32	8,73	4"-3/4	3"-7/16	00625 01 132	
3/8	9,52	5"	3"-5/8	00625 00 38	
7/16	11,11	5"-1/2	4"-1/16	00625 00 716	
1/2	12,70	6"	4"-1/2	00625 00 12	



## Expositor de brocas HSS Rectificadas en Pulgadas



51021P

51029P

Descripción	Art. N°.
Set 21 pz - pcs - uni - tlg Ø 1/16 + 3/8 x 1/64	00625 000 21
Descripción	Art. N°.
Set 29 pz - pcs - uni - tlg Ø 1/16 + 1/2 x 1/64	00625 000 29