



# Broca de percusión SDS-plus

SDS  
plus

4 espirales, con punta de centrado

Ø mm	Long. total mm.	Long. trabajo mm.	Art. Nº.	U/E
4,0	110	50	<b>648 34 110</b>	1/10
4,8	110	50	<b>648 348 110</b>	1
	140	80	<b>648 348 140**</b>	
	160	100	<b>648 348 160**</b>	
	210	150	<b>648 348 210**</b>	
	260	200	<b>648 348 260**</b>	
5,0	110	50	<b>648 35 111</b>	1/10
	160	100	<b>648 35 160</b>	1
5,5	110	50	<b>648 355 110</b>	
	160	100	<b>648 355 160</b>	
6,0	110	50	<b>648 36 110</b>	1/10
	160	100	<b>648 36 160*</b>	1/10
	210	150	<b>648 36 210*</b>	
	260	200	<b>648 36 260*</b>	
6,3	310	260	<b>648 36 310*</b>	
	260	200	<b>648 363 260**</b>	
	285	225	<b>648 363 285**</b>	
	360	300	<b>648 363 360**</b>	
	410	350	<b>648 363 410**</b>	
6,5	110	50	<b>648 365 110</b>	1/10
	160	100	<b>648 365 160*</b>	
	260	200	<b>648 365 260*</b>	
	310	260	<b>648 365 310*</b>	
7,0	160	100	<b>648 37 160</b>	1
	250	200	<b>648 37 250</b>	
8,0	110	50	<b>648 38 110</b>	1/10
	160	100	<b>648 38 160</b>	1/10
	210	150	<b>648 38 210</b>	1/10
	260	200	<b>648 38 260</b>	
	400	350	<b>648 38 400</b>	
	460	400	<b>648 38 460</b>	
600	550	<b>648 38 600</b>	1	
9,0	160	100		<b>648 39 160</b>
	110	50	<b>648 310 110</b>	
10,0	160	100	<b>648 310 160</b>	1/10
	210	150	<b>648 310 210</b>	1/10
	260	200	<b>648 310 260*</b>	
	310	250	<b>648 310 310*</b>	
	350	300	<b>648 310 350*</b>	1
	450	400	<b>648 310 450</b>	
	600	550	<b>648 310 600</b>	
	800	750	<b>648 310 800</b>	
1000	920	<b>648 310 101</b>		

Ø mm	Long. total mm.	Long. trabajo mm.	Art. Nº.	U/E	
11,0	210	150	<b>648 311 210</b>	1/10	
12,0	160	100	<b>648 312 160</b>		1
	210	150	<b>648 312 210</b>		
	260	200	<b>648 312 260</b>		
	360	300	<b>648 312 360</b>		
	450	400	<b>648 312 450</b>		
13,0	600	550	<b>648 312 600</b>	1	
	1000	920	<b>648 312 101</b>		
	260	200	<b>648 313 260</b>		
14,0	160	100	<b>648 314 160</b>	1/10	
	210	150	<b>648 314 210</b>		
	260	200	<b>648 314 260</b>		
	310	260	<b>648 314 310</b>		
	450	400	<b>648 314 450</b>		
	600	550	<b>648 314 600</b>		
	1000	920	<b>648 314 101</b>		
15,0	160	100	<b>648 315 160</b>	1	
	210	150	<b>648 315 210</b>		
	260	200	<b>648 315 260</b>		
	450	400	<b>648 315 450</b>		
16,0	160	100	<b>648 316 160</b>	1	
	210	150	<b>648 316 210</b>		
	260	200	<b>648 316 260</b>		
	450	400	<b>648 316 450</b>		
	600	550	<b>648 316 600</b>		
	800	750	<b>648 316 800</b>		
1000	920	<b>648 316 101</b>			
17,0	210	150	<b>648 317 210</b>	1/10	
18,0	200	150	<b>648 318 200</b>		1
	600	550	<b>648 318 600</b>		
20,0	200	150	<b>648 320 200</b>	1	
	450	400	<b>648 320 450</b>		
	600	550	<b>648 320 600</b>		
22,0	250	200	<b>648 322 250</b>	1	
	450	400	<b>648 322 450</b>		
	600	550	<b>648 322 600</b>		
24,0	600	550	<b>648 240 600</b>	1	
25,0	250	200	<b>648 325 250</b>		

\* Broca especial para tornillos Amo III:

Ø 6,0 y 6,5 para Amo III – 7,5 mm

Ø 10,0 mm para Amo III – 11,5 mm

\*\* Broca especial para sistema de fijación SFS-Spike